

PERMTM CHIP

Granite Chips for Permeable Paver Systems

A PERMEABLE SOLUTION
FROM THE MAKERS OF
Snap Edge® & PermEdge®
OFFERING OPTIMAL
INFILTRATION PERFORMANCE

RESIDENTIAL & COMMERCIAL APPLICATIONS DRIVEWAYS • PATIOS • WALKWAYS • PARKING LOTS

- High-Strength Crushed and Washed Granite
- Meets ASTM #9 Stone Specification
- 100% Fractured Surface
- Freeze/Thaw Resistant
- Tests Well Above Minimum Target of 100 in/hr Infiltration Rate
- Resists Clogging/Particle Build Up in Permeable Pavement Joints
- For Use in Standard or Narrow Joints
- Available in 50 lb. Plastic Bags, 56 Bags Per Pallet and 2500 lb. Super Sacks
- Can Be Stabilized With SB-1000 PICP Chip Stabilizer

INSTALLATION INSTRUCTIONS

- Sweep PermChip into joints
- Sweep pavers clean of any PermChip
- Compact using a vibrating plate compactor – 2 passes
- After compaction, fill all joints to 1/8" from the top of the paver
- Remove any excess PermChip from the paver surface

4 NATURAL STONE COLORS



Eclipse Black



Saturn Tan



Stormy Gray



Sunset Red
Special Order

BENEFITS OF USING PERMCHIP

- Stays In Joints Better Than Rounded Aggregate
- Allows Surface Water Infiltration In Permeable Pavement Systems
- Natural Stone Colors That Complement Many Permeable Pavement Surfaces

PermChip can be used as permeable pavement joint fill, bedding course and as a decorative pathway surface.

COVERAGE RATE PER 50LB BAG OF PERMCHIP

60 MM PAVER

OPENING RATIO	SQ. FT. PER BAG
11%	45
13%	40
15%	35

80 MM PAVER

OPENING RATIO	SQ. FT. PER BAG
11%	35
13%	30
15%	25

These are estimates and could vary based on local conditions

